

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481 ICP Construction Inc.

Version No: 1.4

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **09/28/2023** Print Date: **09/28/2023** S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

1 Todade Individual		
Product name	Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481	
Synonyms	Not Available	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Intumescent Coating
--------------------------	---------------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

Association	on / Organisation	ChemTel
Emer	gency telephone numbers	1-800-255-3924
Other emer	gency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3

Label elements

Hazard pictogram(s)





Signal word

Warning

Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.

Version No: **1.4** Page **2** of **10** Issue Date: **09/28/2023**

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
21645-51-2*	7-13	aluminium hydroxide
56-81-5	1-5	glycerol
14808-60-7*	<0.1	silica crystalline - quartz
13463-67-7*	1-5	Titanium Dioxide Ti02
1333-86-4	1-5	carbon black

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- ► Seek medical attention in event of irritation.

Inhalation

- ▶ If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
 Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained.

Version No: **1.4** Page **3** of **10** Issue Date: **09/28/2023**

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

	Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Special protective equipment a	and precautions for fire-fighters		
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. 		
Fire/Explosion Hazard	Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes.		

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. DO NOT allow clothing wet with material to stay in contact with skin
Other information	
Conditions for safe storage, inc	cluding any incompatibilities
Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer.

• Check all containers are clearly labelled and free from leaks.

SECTION 8 Exposure controls / personal protection

None known

Control parameters

Storage incompatibility

Version No: 1.4 Page 4 of 10 Issue Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	aluminium hydroxide	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	aluminium hydroxide	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	aluminium hydroxide	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	aluminium hydroxide	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	aluminium hydroxide	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	glycerol	Glycerin (mist)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	glycerol	Glycerin (mist)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	glycerol	Glycerin (mist)	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide Ti02	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide Ti02	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
aluminium hydroxide	8.7 mg/m3	73 mg/m3	440 mg/m3
glycerol	45 mg/m3	180 mg/m3	1,100 mg/m3
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3
Titanium Dioxide Ti02	30 mg/m3	330 mg/m3	2,000 mg/m3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
aluminium hydroxide	Not Available	Not Available
glycerol	Not Available	Not Available
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
Titanium Dioxide Ti02	5,000 mg/m3	Not Available
carbon black	1,750 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

 Version No: 1.4
 Page 5 of 10
 Issue Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	1.6

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

Version No: **1.4** Page **6** of **10** Issue Date: **09/28/2023**

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

Hazardous decomposition products

See section 5

SECTION 11 Toxicological information

SECTION IT TOXICOlogical I			
Information on toxicological e	ffects		
Inhaled	The material can cause respiratory irritation in some persons. The both The material has NOT been classified by EC Directives or other clast corroborating animal or human evidence.	ody's response to such irritation can cause further lung damage. sification systems as "harmful by inhalation". This is because of the lack of	
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	This material can cause eye irritation and damage in some persons.		
Chronic	There has been concern that this material can cause cancer or muta Repeated or long-term occupational exposure is likely to produce cult Long-term exposure to respiratory irritants may result in airways dise	mulative health effects involving organs or biochemical systems.	
Fireshall Haility Coard SS4474	TOXICITY	IRRITATION	
Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481	Not Available	Not Available	
	TOWNER	IDDITATION	
aluminium hudvavida	Intraperitoneal (Rat) LD: 150 mg/kg ^[2]	IRRITATION Eye: no adverse effect observed (not irritating) ^[1]	
aluminium hydroxide	Intrapentorieal (Nat) ED. 130 Hig/kg ^c 2	Skin: no adverse effect observed (not irritating)[1]	
	TOXICITY	IRRITATION	
glycerol	dermal (guinea pig) LD50: 58500 mg/kg ^[1]	Not Available	
	Inhalation(Rat) LC50: >5.85 mg/L4h ^[1]		
	Oral (Mouse) LD50; 4090 mg/kg ^[2]		
	TOXICITY	IRRITATION	
silica crystalline - quartz	Inhalation (Human)LCLo: 0.3 mg/m3/10Y ^[2]	Not Available	
Sinca crystalline - quartz	Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y ^[2]		
	Inhalation (Rat)TCLo: 50 mg/m3/6H/71W ^[2]		
	TOXICITY	IRRITATION	
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	
Titanium Dioxide Ti02	Inhalation(Rat) LC50: >2.28 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]	
	Oral (Rat) LD50: >=2000 mg/kg ^[1]		
	TOXICITY	IRRITATION	
carbon black	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]	
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acut specified data extracted from RTECS - Register of Toxic Effect of chemical specified data.	e toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise emical Substances	
GLYCEROL	At very high concentrations, evidence predicts that glycerol may cause tremor, irritation of the skin, eyes, digestive tract and airway. Otherwise it is of low toxicity. There is no significant evidence to suggest that it causes cancer, genetic, reproductive or developmental toxicity.		
	WARNING: For inhalation exposure ONLY: This substance has been		
silica crystalline - quartz	The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as bein carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lui disease.		
	Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours.		
	* Millions of particles per cubic foot (based on impinger samples cou NOTE : the physical nature of quartz in the product determines whether		

Version No: 1.4 Page **7** of **10** Issue Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

OARDON DI AOK	Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported			
CARBON BLACK WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.			ogenic to Humans.	
Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481 & GLYCEROL	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.			
aluminium hydroxide & CARBON BLACK	No significant acute toxicological data identified in literature search.			
Acute Toxicity	×	Carcinogenicity	✓	
Skin Irritation/Corrosion	✓	Reproductivity	×	
Serious Eye Damage/Irritation	✓ STOT - Single Exposure ✓			
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure		
Mutagenicity	×	Aspiration Hazard	×	

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

Fireshall Hillity Cyard SS4 474	Endpoint	Test Duration (hr)		Species		Value	Source
Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481	Not Available	Not Available		Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)		Species		Value	Source
	EC50	72h		Algae or other aquatic plants		0.017mg/L	2
	EC50	48h		Crustacea		>0.065mg/l	4
aluminium hydroxide	EC50	96h		Algae or other aquatic plants		0.005mg/L	2
	NOEC(ECx)	72h		Algae or other aquatic plants		>100mg/l	1
	LC50	96h		Fish		0.57mg/l	2
	Endpoint	Test Duration (hr)		Species		Value	Source
glycerol	LC50	96h		Fish		>11mg/L	2
	EC0(ECx)	24h		Crustacea		>500mg/l	1
silica crystalline - quartz Not	Endpoint	Test Duration (hr)		Species		Value	Source
	Not Available	Not Available		Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)		Species		Value	Source
	BCF	1008h		Fish		<1.1-9.6	7
	EC50	72h		Algae or other aquatic plants		3.75-7.58mg/l	4
Titanium Dioxide Ti02	EC50	48h		Crustacea		1.9mg/l	2
	EC50	96h		Algae or other aquatic plants		179.05mg/l	2
	LC50	96h		Fish		1.85-3.06mg/l	4
	NOEC(ECx)	672h		Fish		>=0.004mg/L	2
	Endpoint	Test Duration (hr)	S	pecies	Val	lue	Source
	EC50	72h	A	lgae or other aquatic plants	>0.	.2mg/l	2
carbon black	EC50	48h	С	rustacea	33.	.076-41.968mg/l	4
	LC50	96h	Fi	ish	>10	00mg/l	2
	NOEC(ECx)	24h	С	rustacea	320	00mg/l	1
Legend:	Ecotox databas	1. IUCLID Toxicity Data 2. Europe E se - Aquatic Toxicity Data 5. ECETOC ion Data 8. Vendor Data					

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
glycerol	LOW	LOW

 Version No: 1.4
 Page 8 of 10
 Issue Date: 09/28/2023

 Print Date: 09/28/2023
 Print Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Ingredient	Persistence: Water/Soil	Persistence: Air
Titanium Dioxide Ti02	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation		
glycerol	LOW (LogKOW = -1.76)		
Titanium Dioxide Ti02	LOW (BCF = 10)		

Mobility in soil

Ingredient	Mobility		
glycerol	HIGH (KOC = 1)		
Titanium Dioxide Ti02	LOW (KOC = 23.74)		

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).

SECTION 14 Transport information

Labels Required

Marina Dellutant	NO
Marine Pollutant	I NO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
aluminium hydroxide	Not Available
glycerol	Not Available
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available
carbon black	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
aluminium hydroxide	Not Available
glycerol	Not Available
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available
carbon black	Not Available

SECTION 15 Regulatory information

Version No: 1.4 Page 9 of 10 Issue Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

aluminium hydroxide is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

glycerol is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

Titanium Dioxide Ti02 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US OSHA Permissible Exposure Limits (PELs) Table Z-3 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No

Version No: 1.4 Page 10 of 10 Issue Date: 09/28/2023

Fireshell Utility Guard SS1474, SS1475, SS1481, SS1481

Print Date: 09/28/2023

Serious eye damage or eye irritation		Yes
Specific target organ toxicity (single or repeated exposure)		No
Aspiration Hazard		No
Germ cell mutagenicity		No
Simple Asphyxiant		No
Hazards Not Otherwise Classified		No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65



MARNING: This product can expose you to chemicals including silica crystalline - quartz, Titanium Dioxide Ti02, carbon black, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (aluminium hydroxide; glycerol; silica crystalline - quartz; Titanium Dioxide Ti02; carbon black)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	09/28/2023
Initial Date	09/27/2023

CONTACT POINT

SDS Version Summary

Version	Date of Update	Sections Updated
0.4	09/28/2023	Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, Toxicological information - Chronic Health, Hazards identification - Classification, Ecological Information - Environmental, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (fire/explosion hazard), Composition / information on ingredients - Ingredients, Handling and storage - Storage (storage incompatibility)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Powered by AuthorlTe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**